



Scotchcal™ Graphic Film IJ37-10

for Piezo Ink Jet Printing

Description

Advantages

- Excellent image performance with solvent based piezo ink jet printers
- Excellent hiding power
- Matching overlaminates for graphic protection and higher UV-resistance

Product Line

IJ37-10	white gloss, permanent adhesive (grey colored)
---------	--

Characteristics

This information is subject to change. These values are typical for unprinted film and are not intended for use in specifications. Be sure this is the most current Product Bulletin. See **3M Related Literature** at the end of this bulletin.

Characteristic	Description
Film	3 mil (75µm), white vinyl (polymeric)
Thickness (film and adhesive)	85 - 95 µm
Adhesive type and color	Pressure sensitive, permanent, solvent based acrylic, light gray
Liner	140 g/m ² , coated paper
Application surface	Flat
Application substrates	Glass, metal, paint, rigid plastic
Minimum application temperature (air and substrate)	10°C
Removal	Removable within the warranted durability of the product
Service temperature range	-50°C to +90°C
Tensile strength (min)	130%
Applied shrinkage	< 0.5 mm
Adhesion (FINAT TM-1, stainless steel, 200 mm/min)	> 18 N/25 mm
Shelf life	2 years after receipt from 3M (dry conditions, Temp. < 38°C)

Effective Performance Life

When manufactured, applied and maintained in accordance with 3M recommended procedures, graphics produced on 3M™ Scotchcal™ Graphic Film IJ37-10 and protected with selected 3M™ Scotchcal™ Overlaminates a guarantee founded on 3M™ Performance Guarantee will be given by 3M. Performance statements are based upon representative experience obtained from testing throughout Europe. Actual performance will be determined by substrate selection and preparation, maintenance of the marking and exposure conditions.

When to Use an Overprint Clear or Overlamine

An overprint clear or overlamine provides protection to a graphic as well as changing gloss. Typically, only graphics that are subjected to harsh conditions require this protection in order to be warranted. They include:

- Vehicle and fleet graphics; such graphics are subjected to abrasion such as road debris and automatic/power washing.
- Any graphic exposed to abrasive washing conditions, including automatic/power washing, harsh cleaners or chemicals.

Warranted Durability

The 3M Performance Guarantee statement for Scotchcal™ Graphics Film IJ37-10 is based on chosen media construction.

Please refer to the European Performance Guarantee chart for details. The guaranty chart is available on request from your local 3M contact.

Limitations of End Uses

Specifically, we do not warrant this film for the following:

- Graphics applied to:
 - Corrugated or highly-irregular surfaces or sharply raised areas such as huck bolts
 - Substrates that do not have a clean, smooth surface or have poor paint-to-substrate adhesion
 - Stainless steel
 - Flexible substrates
 - Compound contours
 - Exterior horizontal applications
- Graphic removal from:
 - Existing graphics that must remain intact
- Graphics subjected to gasoline vapours or spills

Application Tapes

Overlamine or Overprint Clear	Prespace Tape	Premask Tape
Printed, uncleared	SCPS-100	SCPM-19
1920DR SC8019 / SC8020 8530	SCPS-100	SCPM-19

See Instruction Bulletin 4.3 for details.

Removal

Graphic Films IJ37-10 is designed for permanent application.

Important Notice

This bulletin provides technical information only.

All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.

Before using, the user must determine the suitability of the product for its required or intended use, and the user assumes all risk and liability whatsoever in connection therewith.

3M Related Literature

3M offers for all products detailed technical literature. Additionally, comprehensive instruction bulletins are available describing in detail the best usage of our products.

Ask your local 3M contact or refer to local Commercial Graphics internet pages to get the most current product and/or instruction bulletins.

For Further Assistance

For help on specific questions relating to 3M Commercial Graphics products, please contact your local 3M Technical Service person or contact:

3M Deutschland GmbH
Commercial Graphics Division
Carl-Schurz-Strasse 1
D-41453 Neuss
Germany
Phone +49 (0) 2131 14 3500
Fax +49 (0) 2131 14 2377

The use of trademark signs and brand names in this bulletin is based upon US standards. These standards may vary from country to country outside the USA.